

5878

WIRELESS WALL TRANSMITTER/REMOTE



Honeywell's easy-to-operate, quick install wireless solution provides convenient fingertip control of alarm systems, lights or garage doors. The 5878 performs the same functions as other four-button keyfobs while

providing the added convenience of two extra buttons to control lamp modules and a two-button panic. It is compatible with all 5800 Series Wireless Receivers.

FEATURES

- Six buttons, eight loops (Two serial numbers with four loops)
- Sleek, super thin design
- Mounts to single-ganged box (screws included), double-sided tape (included) or hides in a drawer
- LED blinks to confirm that signal has been sent
- User replaceable lithium coin cell battery included
- Extra buttons make it easy to control lamp modules
- Extra button inserts for easy customization

SPECIFICATIONS

- **Dimensions**
 - 4.50" x 2.75" x .25"
- **Transmit Frequency**
 - 345 MHz
- **Temperature Range**
 - 10°F to 120°F (-12°C to 149°C)
 - Indoor use only
- **Battery**
 - 3V Lithium
- **Wireless Range**
 - Up to 200 ft.
- **Compatibility**
 - Compatible with all 5800 Series Wireless Receivers, VISTA and LYNX panels

ORDERING

5878

Wireless Wall Transmitter/Remote

Honeywell Security & Custom Electronics

Honeywell International Inc.
PO Box 9035
Syosset, NY 11791
1-800-467-5875

www.honeywell.com

PL06012
L/5878DS/D
October 2006
© 2006 Honeywell International Inc.

Honeywell